

Cam follower CR28-VUU-IKO - CR28-VUU-IKO

<https://www.123bearing.ie/bearing-housing/deep-groove-bearing/cam-follower/cr28-vuu-iko>

IKO

CAM FOLLOWERS

Inch Series Cam Followers Full Complement Type/With Screwdriver Slot



Stud dia. mm (inch)	Identification number				Mass (Ref.) g	D	C	d ₁	G UNF	G ₁
	Shield type With cover outer ring	Shield type With cylindrical outer ring	Spigot type With drilled outer ring	Spigot type With cylindrical outer ring						
19.050 ($\frac{3}{4}$)				CR 28 VUU	372	44.450 ($\frac{1 1/2}$)	25.400 (1)	19.050 ($\frac{3}{4}$)	$\frac{1}{2}$ -16	22.225 ($\frac{7}{8}$)
Boundary dimensions mm(inch)					Mounting dimension f Min. mm(inch)	Maximum tightening torque N·m	Basic dynamic load rating C N	Basic static load rating C ₀ N		
B max	B ₂	B ₃	C ₁	g ₁					g ₂	r
25.8100	44.450 ($\frac{1 1/2}$)	11.112 ($\frac{7}{16}$)	0.794 ($\frac{1}{16}$)	4.762 ($\frac{3}{16}$)	3.969 ($\frac{5}{32}$)	1.588 ($\frac{1}{16}$)	32.543 ($\frac{1 1/8}$)	100	35 300	55 800

PRODUCT FEATURES

Brand	IKO
N° Ean13	3616060464057
Inside diameter	19.05 mm
Outside diameter	44.45 mm
Thickness	25.4 mm
Weight	372 g
Packaging	1

contact@123bearing.ie

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE