

SI Rod end

SIL14-T-K-DURBAL - SIL14-T-K-DURBAL

<https://www.123bearing.ie/bearing-housing/rod-end/si/sil14-t-k-durbal>


SIL14-T-K



female thread:
maintenance free,
according to
DIN ISO 12240-4,
series K



Description: DIN ISO rod end K series. Made of spherical plain bearing DG...PW pressed into rod end body. Sliding combination steel / bronze-PTFE composite.



Rod end body:
surface zinc plated

Sliding combination:
steel / bronze-PTFE composite

Inner ring:
bearing steel, hardened, ground and
spherical surface chromium plated

Outer ring:
brass body pressed around, outer race
lined with bronze-PTFE composite

Lubrication:
maintenance free

order number	measurement (mm)
right hand thread	d G B C1 d2 d3 d4
left hand thread	
SIL 14 T/K	14 M 14 19 13,50 36 20,0 25

type	measurement (mm)			load rating C ₀ (N)	weight (kg)
	l ₁ min	W	h		
SI / SIL 14 T/K	25	22	57	16	31,0

PRODUCT FEATURES

Brand	DURBAL
N° Ean13	3663952489339
Inside diameter	14 mm
Outside diameter	36 mm
Thickness	19 mm
Type	SI
Weight	160 g
Thread	Left-hand thread
Lubrication	without
Packaging	1

contact@123bearing.ie

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE