

## SI Rod end

### SIL14-T-K-DURBAL - DSIL14-T-K-DURBAL

<https://www.123bearing.ie/bearing-housing/rod-end/si/dsil14-t-k-durbal>


#### SIL14-T-K



female thread:  
maintenance free,  
according to  
DIN ISO 12240-4,  
series K



**Description:** DIN ISO rod end K series. Made of spherical plain bearing DG...PW pressed into rod end body. Sliding combination steel / bronze-PTFE composite.



**Rod end body:**  
surface zinc plated

**Sliding combination:**  
steel / bronze-PTFE composite

**Inner ring:**  
bearing steel, hardened, ground and spherical surface chromium plated

**Outer ring:**  
brass body pressed around, outer race lined with bronze-PTFE composite

**Lubrication:**  
maintenance free

order number	right hand thread	left hand thread	d	G	B	C <sub>1</sub>	d <sub>2</sub>	d <sub>3</sub>	d <sub>4</sub>
SIL 14 T/K			14	M 14	19	13,50	36	20,0	25

type	measurement (mm)			h	d <sub>1</sub>	load rating C <sub>10</sub> (N)	weight (kg)
	l <sub>1</sub> min	W					
SI / SIL 14 T/K	25	22	57	16	31,0	0,160	

## PRODUCT FEATURES

Brand	DURBAL
N° Ean13	3663952489339
Inside diameter	14 mm
Outside diameter	36 mm
Thickness	19 mm
Type	SI
Weight	160 g
Thread	Left-hand thread
Lubrication	without
Packaging	1

[contact@123bearing.ie](mailto:contact@123bearing.ie)

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE