

## SI Rod end SI18-T-K-DURBAL - SI18-T-K-DURBAL

<https://www.123bearing.ie/bearing-housing/rod-end/si/si18-t-k-durbal>


### SI18-T-K



female thread:  
maintenance free,  
according to  
DIN ISO 12240-4,  
series K



**Description:** DIN ISO rod end K series. Made of spherical plain bearing DG...PW pressed into rod end body. Sliding combination steel / bronze-PTFE composite.



**Rod end body:**  
surface zinc plated

**Sliding combination:**  
steel / bronze-PTFE composite

**Inner ring:**  
bearing steel, hardened, ground and spherical surface chromium plated

**Outer ring:**  
brass body pressed around, outer race lined with bronze-PTFE composite

**Lubrication:**  
maintenance free

order number		measurement [mm]						
right hand thread	left hand thread	d	G	B	C <sub>1</sub>	d <sub>2</sub>	d <sub>3</sub>	d <sub>4</sub>
SI 18 TIK		18	M 18 x 1,5	23	16,50	44	25,0	31

type	measurement [mm]			load rating C <sub>10</sub> [N]	weight [kg]
	l <sub>1</sub> min	W	h		
SI / SI18 TIK	32	27	71	15	0,320

## PRODUCT FEATURES

Brand	DURBAL
N° Ean13	3663952489520
Inside diameter	18 mm
Outside diameter	44 mm
Thickness	23 mm
Type	SI
Weight	320 g
Thread	Right-hand thread
Lubrication	without
Packaging	1

[contact@123bearing.ie](mailto:contact@123bearing.ie)

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE