

SA Rod end SAL50-T-K-DURBAL - SAL50-T-K-DURBAL

<https://www.123bearing.ie/bearing-housing/rod-end/sa/sal50-t-k-durbal>

SAL50-T-K



Description: DIN ISO rod end K series. Made of spherical plain bearing DG...PW pressed into rod end body. Sliding combination steel / bronze-PTFE composite.

male thread: maintenance free, according to DIN ISO 12240-4, series K

rod end body: surface zinc plated

Sliding combination: steel / bronze-PTFE composite

inner ring: bearing steel, hardened, ground and spherical surface chromium plated

Outer ring: brass body pressed around, outer race lined with bronze-PTFE composite

Lubrication: maintenance free

order number		measurement [mm]				
right hand thread	left hand thread	d	G	B	C ₁	d ₂
SAL 50 T/K		50	M 48 x 2	60	45,00	117

type	measurement [mm]		h	α [°]	Tragzahlen C ₁₀ [KN]	weight [kg]
	l ₁ min	l ₂				
SA / SAL 50 T/K	105	59	185	12		4,800

PRODUCT FEATURES

Brand	DURBAL
N° Ean13	3663952490496
Inside diameter	50 mm
Outside diameter	117 mm
Thickness	60 mm
Type	SA
Weight	4800 g
Thread	Left-hand thread
Lubrication	without
Packaging	1

contact@123bearing.ie

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE