

## SA Rod end SSAL8-T-K-DURBAL - DSSAL8-T-K-DURBAL

<https://www.123bearing.ie/bearing-housing/rod-end/sa/dssal8-t-k-durbal>

### SSAL8-T-K



**male thread:** maintenance free, according to DIN ISO 12240-4, series K, in stainless steel

**Description:** DIN ISO rod end K series. Made of spherical plain bearing DG...PW pressed into rod end body. Sliding combination steel / bronze-PTFE composite.

**rod end body:** stainless steel

**Sliding combination:** steel / bronze-PTFE composite

**inner ring:** stainless steel, hardened and ground

**Outer ring:** stainless steel body pressed around, outer race lined with bronze-PTFE composite

**Lubrication:** maintenance free

order number	right hand thread	left hand thread	measurement [mm]				
SSAL 8 T/K	8	M 8	12	9,00	24		

type	measurement [mm]		h	alpha [°]	load rating C <sub>0</sub> [kN]	weight [kg]
	i, min	i <sub>2</sub> min				
SSA / SSAL 8 T/K	25	42	14	12,9	0,038	

## PRODUCT FEATURES

Brand	DURBAL
N° Ean13	3663952490632
Inside diameter	8 mm
Outside diameter	24 mm
Thickness	12 mm
Type	SA
Weight	38 g
Thread	Left-hand thread
Lubrication	without
Packaging	1

[contact@123bearing.ie](mailto:contact@123bearing.ie)

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE