

# SI Rod end SSIL20-T-K-DURBAL - SSIL20-T-K-DURBAL

<https://www.123bearing.ie/bearing-housing/rod-end/si/ssil20-t-k-durbal>

## SSIL20-T-K



**female thread:** maintenance free, according to DIN ISO 12240-4, series K, in stainless steel

**Description:** DIN ISO rod end K series. Made of spherical plain bearing DG...PW pressed into rod end body. Sliding combination steel / bronze-PTFE composite.

**Rod end body:** stainless steel

**Sliding combination:** steel / bronze-PTFE composite

**Inner ring:** stainless steel, hardened and ground

**Outer ring:** stainless steel body pressed around, outer race lined with bronze-PTFE composite

**Lubrication:** maintenance free

order number	right hand thread	left hand thread	measurement [mm]							
SSIL 20 T/K			d	G	B	C1	d1	d2	d3	d4
			20	M 20 x 1,5	25	18,00	50	27,5	34	

type	measurement [mm]			α °FS	load rating C <sub>0</sub> [kN]	weight [kg]
	l <sub>1</sub> min	W	h			
SSI / SSIL 20 T/K	33	30	77	14	57,0	0,420

## PRODUCT FEATURES

Brand	DURBAL
N° Ean13	3663952491561
Inside diameter	20 mm
Outside diameter	50 mm
Thickness	25 mm
Type	SI
Weight	420 g
Thread	Left-hand thread
Lubrication	without
Packaging	1

[contact@123bearing.ie](mailto:contact@123bearing.ie)

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE