

SI Rod end SSI28-T-K-DURBAL - DSSI28-T-K-DURBAL

<https://www.123bearing.ie/bearing-housing/rod-end/si/dssi28-t-k-durbal>

SSI28-T-K



female thread: maintenance free, according to DIN ISO 12240-4, series K, in stainless steel

Description: DIN ISO rod end K series. Made of spherical plain bearing DG...PW pressed into rod end body. Sliding combination steel / bronze-PTFE composite.

Rod end body: stainless steel

Sliding combination: steel / bronze-PTFE composite

Inner ring: stainless steel, hardened and ground

Outer ring: stainless steel body pressed around, outer race lined with bronze-PTFE composite

Lubrication: maintenance free

order number	right hand thread	left hand thread	measurement [mm]					
SSI 28 T/K	28	M 27 x 2	35	24,00	66	37,0	46	

type	measurement [mm]			α °FS	load rating C ₀ [kN]	weight [kg]
	l _s min	W	h			
SSI / SSI 28 T/K	51	41	103	15	107,0	0,820

PRODUCT FEATURES

Brand	DURBAL
N° Ean13	3663952491684
Inside diameter	28 mm
Outside diameter	66 mm
Thickness	35 mm
Type	SI
Weight	820 g
Thread	Right-hand thread
Lubrication	without
Packaging	1

contact@123bearing.ie

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE