

SI Rod end SSIL30M27X2-T-K-DURBAL - SSIL30M27X2-T-K-DURBAL

<https://www.123bearing.ie/bearing-housing/rod-end/si/ssil30m27x2-t-k-durbal>

SSIL30M27X2-T-K



female thread: maintenance free, according to DIN ISO 12240-4, series K, in stainless steel

Description: DIN ISO rod end K series. Made of spherical plain bearing DG...PW pressed into rod end body. Sliding combination steel / bronze-PTFE composite.

Red end body: stainless steel

Sliding combination: steel / bronze-PTFE composite

Inner ring: stainless steel, hardened and ground

Outer ring: stainless steel body pressed around, outer race lined with bronze-PTFE composite

Lubrication: maintenance free

order number	right hand thread	left hand thread	measurement [mm]							
SSIL 30 TIK M 27 x 2			d	G	B	C ₁	d ₁	d ₂	d ₃	d ₄
			30	M 27 x 2	37	25,00	70	40,0	50	

type	measurement [mm]				α °FS	load rating C ₀ [kN]	weight [kg]
	l _s min	W	h				
SSI / SSIL 30 TIK M 27 x 2	51	41	110	17	114,0	1,100	

PRODUCT FEATURES

Brand	DURBAL
N° Ean13	3663952491738
Inside diameter	30 mm
Outside diameter	70 mm
Thickness	37 mm
Type	SI
Weight	1100 g
Thread	Left-hand thread
Lubrication	without
Packaging	1

contact@123bearing.ie

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE