

SI Rod end DSIL8-PK-DURBAL - SIL8-PK-DURBAL

<https://www.123bearing.ie/bearing-housing/rod-end/si/sil8-pk-durbal>

DSIL8-PK



female thread; maintenance free, according to DIN ISO 12240-4, series K

Description: DIN ISO rod end K series. Sliding combination steel / bronze-PTFE composite.

rod end body: surface case plated

Sliding combination: steel / bronze-PTFE composite

inner ring: bearing steel hardened and ground

Outer ring: rod end body pressed around, outer race lined with bronze-PTFE composite

Lubrication: maintenance free

order number	measurement (mm)	
right hand thread	8	12
DSIL 8 PK	8 M 8	9,00 25 12,5 16

type	measurement (mm)				load rating C ₀ [kN]	weight [kg]
	l ₁ min	W	h	α [°]		
DSI / DSIL 8 PK	16	14	36	12	12,90	0,047

PRODUCT FEATURES

Brand	DURBAL
N° Ean13	3663952491875
Inside diameter	8 mm
Outside diameter	25 mm
Thickness	12 mm
Type	SI
Weight	47 g
Thread	Left-hand thread
Lubrication	without
Packaging	1

contact@123bearing.ie

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE