

## SA Rod end SA22-BK-DURBAL - SA22-BK-DURBAL


<https://www.123bearing.ie/bearing-housing/rod-end/sa/sa22-bk-durbal>

### SA22-BK



male thread;  
maintenance free,  
according to  
DIN ISO 12240-4,  
series K

Description: DIN ISO rod end K series. Sliding combination steel / bronze-PTFE composite.



Rod end body:  
surface zinc plated

Sliding combination:  
steel / bronze-PTFE composite

Inner ring:  
bearing steel hardened and ground

Outer ring:  
rod end body pressed around, outer race  
lined with bronze-PTFE composite

Lubrication:  
maintenance free

order number	measurement [mm]		C <sub>1</sub>	d <sub>2</sub>
	right hand thread	left hand thread		
SA 22 BK	22	M 22 x 1,5	28	55

type	measurement [mm]		α [°]	load rating C <sub>0</sub> [kN]	weight [kg]
	l <sub>1</sub> min	h			
SA / SA 22 BK	50	84	15	68,00	0,480

## PRODUCT FEATURES

Brand	DURBAL
N° Ean13	3663952492704
Inside diameter	22 mm
Outside diameter	55 mm
Thickness	28 mm
Type	SA
Weight	480 g
Thread	Right-hand thread
Lubrication	without
Packaging	1

[contact@123bearing.ie](mailto:contact@123bearing.ie)

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE