

SA Rod end GAL20-UK-DURBAL - GAL20-UK-DURBAL

<https://www.123bearing.ie/bearing-housing/rod-end/sa/gal20-uk-durbal>


GAL20-UK



male thread:
maintenance free,
according to
DIN ISO 12240-4,
series E



Description: DIN ISO rod end E series. Made of spherical plain bearing DGE...UK (UK-2RS) pressed into rod end body. Sliding combination steel / bronze-PTFE composite. Bore diameter $d \geq$ size 35 with additional seal on both sides (e.g. DGAR... UK-2RS) bore diameter $d \geq$ size 17 additional seal on both sides upon request.



Rod end body:
surface zinc plated

Sliding combination:
steel / bronze-PTFE fabric

Inner ring:
bearing steel, hardened, ground and
spherical surface chromium plated

Outer ring:
steel body ground around, outer race
lined with bronze-PTFE composite

Lubrication:
no lubrication necessary,
maintenance free

| order number | d | G | measurement (mm) | C ₁ | d ₂ |
|---|----|------------|------------------|----------------|----------------|
| right hand thread left hand thread GAL 20 UK | 20 | M 20 x 1,5 | 16 | 13,0 | 53 |

| type | l ₁ min | measurement (mm) l ₂ min | h | α [°] | load rating C ₀ (kN) | weight (kg) |
|-----------------|--------------------|--|----|-------|------------------------------------|----------------|
| GAR / GAL 20 UK | 43 | 27 | 78 | 9 | 60,0 | 0,310 |

PRODUCT FEATURES

| | |
|------------------|------------------|
| Brand | DURBAL |
| N° Ean13 | 3663952493107 |
| Inside diameter | 20 mm |
| Outside diameter | 53 mm |
| Thickness | 16 mm |
| Type | SA |
| Weight | 310 g |
| Thread | Left-hand thread |
| Lubrication | without |
| Packaging | 1 |

contact@123bearing.ie

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE