

GE Rod end GAR35-UK-2RS-DURBAL - DGAR35-UK-2RS-DURBAL

<https://www.123bearing.ie/bearing-housing/rod-end/ge/dgar35-uk-2rs-durbal>


GAR35-UK-2RS



male thread:
maintenance free,
according to
DIN ISO 12240-4,
series E



Description: DIN ISO rod end E series. Made of spherical plain bearing DGE...UK (UK-2RS) pressed into rod end body. Sliding combination steel / bronze-PTFE composite. Bore diameter $d \geq$ size 35 with additional seal on both sides (e.g. DGAR... UK-2RS) bore diameter $d \geq$ size 17 additional seal on both sides upon request.



Rod end body:
surface zinc plated

Sliding combination:
steel / bronze-PTFE fabric

Inner ring:
bearing steel, hardened, ground and
spherical surface chromium plated

Outer ring:
steel body ground around, outer race
lined with bronze-PTFE composite

Lubrication:
no lubrication necessary,
maintenance free

order number	measurement (mm)	
right hand thread	d	G
left hand thread	s	C1
GAR 35 UK-2RS	35	M 36 x 3
	25	21,0
		82

type	l, min	measurement [mm]	h	alpha [°]	load rating C ₀ [kN]	weight [kg]
GAR / GAL 35 UK-2RS	82	42	140	6	146,0	1,400

PRODUCT FEATURES

Brand	DURBAL
N° Ean13	3616060467621
Inside diameter	35 mm
Outside diameter	82 mm
Thickness	25 mm
Type	GE
Weight	1400 g
Thread	Right-hand thread
Lubrication	without
Packaging	1
Standard	No standard

contact@123bearing.ie

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE