

# SI Rod end GIR30-UK-2RS-DURBAL - GIR30-UK-2RS-DURBAL

<https://www.123bearing.ie/bearing-housing/rod-end/si/gir30-uk-2rs-durbal>

## GIR30-UK-2RS



female thread:  
maintenance free,  
according to  
DIN ISO 12240-4;  
series E

**Description:** DIN ISO rod end E series. Made of spherical plain bearing DGE...UK (UK-2RS) pressed into rod end body. Sliding combination steel / bronze-PTFE composite. Bore diameter  $d \geq$  size 35 with additional seal on both sides (e.g. DGR... UK-2RS) bore diameter  $d \geq$  size 17 additional seal on both sides upon request.


rod end body:  
surface zinc plated

Sliding combination:  
steel / bronze-PTFE fabric

inner ring:  
bearing steel, hardened, ground and  
spherical surface chromium plated

outer ring:  
steel body pressed around, outer race  
lined with bronze-PTFE composite

Lubrication:  
no lubrication necessary,  
maintenance free



order number	measurement [mm]						
right hand thread	d	G	B	C <sub>1</sub>	d <sub>2</sub>	d <sub>3</sub>	d <sub>4</sub>
GIR 30 UK (-2RS)	30	M 30 x 2	22	19,0	73	40,0	50
type	measurement [mm]			load rating	weight		
	t <sub>3</sub> min	h	W	C <sub>0</sub> [kN]	[kg]		
GIR / GIR 30 UK	56	110	41	6	110,0	0,930	

## PRODUCT FEATURES

Brand	DURBAL
N° Ean13	3663952494012
Inside diameter	30 mm
Outside diameter	73 mm
Thickness	22 mm
Type	SI
Weight	930 g
Thread	Right-hand thread
Lubrication	without
Packaging	1

[contact@123bearing.ie](mailto:contact@123bearing.ie)

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE