

# SI Rod end GIL60-UK-2RS-DURBAL - GIL60-UK-2RS-DURBAL

<https://www.123bearing.ie/bearing-housing/rod-end/si/gil60-uk-2rs-durbal>

## GIL60-UK-2RS



**female thread:** maintenance free, according to DIN ISO 12240-4; series E

**Description:** DIN ISO rod end E series. Made of spherical plain bearing DGE...UK (UK-2RS) pressed into rod end body. Sliding combination steel / bronze-PTFE composite. Bore diameter  $d \geq$  size 35 with additional seal on both sides (e.g. DGR... UK-2RS) bore diameter  $d \geq$  size 17 additional seal on both sides upon request.

**Sliding combination:** steel / bronze-PTFE fabric

**Rod end body:** surface zinc plated

**Inner ring:** bearing steel, hardened, ground and spherical surface chromium plated

**Outer ring:** steel body pressed around, outer race lined with bronze-PTFE composite

**Lubrication:** no lubrication necessary, maintenance free

order number	d	G	B	C <sub>1</sub>	d <sub>2</sub>	d <sub>3</sub>	d <sub>4</sub>
GIL 60 UK-2RS	60	M 52 x 3	44	38,0	135	70,0	88

type	measurement [mm]			$\alpha$ [°]	load rating C <sub>0</sub> [kN]	weight [kg]
	t <sub>3</sub> min	h	W			
GIR / GIL 60 UK-2RS	70	175	75	6	450,0	5,500

## PRODUCT FEATURES

Brand	DURBAL
N° Ean13	3663952494258
Inside diameter	60 mm
Outside diameter	135 mm
Thickness	44 mm
Type	SI
Weight	5500 g
Thread	Left-hand thread
Lubrication	without
Packaging	1

[contact@123bearing.ie](mailto:contact@123bearing.ie)

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE