

SI Rod end GIR70-UK-2RS-DURBAL - GIR70-UK-2RS-DURBAL

<https://www.123bearing.ie/bearing-housing/rod-end/si/gir70-uk-2rs-durbal>

GIR70-UK-2RS



female thread:
maintenance free,
according to
DIN ISO 12240-4;
series E


Description: DIN ISO rod end E series. Made of spherical plain bearing DGE...UK (UK-2RS) pressed into rod end body. Sliding combination steel / bronze-PTFE composite. Bore diameter $d \geq$ size 35 with additional seal on both sides (e.g. DGR... UK-2RS) bore diameter $d \geq$ size 17 additional seal on both sides upon request.

Sliding combination:
steel / bronze-PTFE fabric

Inner ring:
bearing steel, hardened, ground and spherical surface chromium plated

Outer ring:
steel body pressed around, outer race lined with bronze-PTFE composite

Lubrication:
no lubrication necessary,
maintenance free



order number	measurement [mm]	
GIR 70 UK-2RS	d	G
	B	C ₁
	d ₂	d ₃
	d ₄	h
	W	

type	measurement [mm]			load rating	weight
	t _{3 min}	h	W	C ₀ [kN]	[kg]
GIR / GIR 70 UK-2RS	80	200	85	610,0	8,600

PRODUCT FEATURES

Brand	DURBAL
N° Ean13	3663952494296
Inside diameter	70 mm
Outside diameter	160 mm
Thickness	49 mm
Type	SI
Weight	8600 g
Thread	Right-hand thread
Lubrication	without
Packaging	1

contact@123bearing.ie

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE