

SI Rod end SIZJL6-DURBAL - SIZJL6-DURBAL

<https://www.123bearing.ie/bearing-housing/rod-end/si/sizjl6-durbal>

SIZJL6



female thread:
lubrication
required,
similar to
DIN ISO 12240-4,
series K,
measurement in
inches

Description: DIN ISO rod end K series. Dimensions
in inch. Sliding combination steel / steel.
Size ≥ 9 with grease nipple can be mounted upon
request.

Rod end body:
surface zinc plated

Sliding combination:
steel / steel

Inner ring:
bearing steel, hardened, ground and
spherical surface chromium plated

Outer ring:
rod end body pressed around inner ring

Lubrication:
lubrication required

order number		measurement [mm]						
right hand thread	left hand thread	d	B	C ₁	d ₂	G	d ₃	d ₄
SIZJL 6		6,35	9,53	6,35	19,05	1/4 - 28	9,15	11,91

type	inches	l ₁ min	measurement [mm]		α	load rating	weight
			W	h	[°]	C ₀ (KN)	[g]
SIZJ / SIZJL 6	1 / 4 "	15,88	9,53	33,32	13,5	9,6	0,023

PRODUCT FEATURES

Brand	DURBAL
N° Ean13	3663952496702
Inside diameter	6.35 mm
Outside diameter	19.05 mm
Thickness	9.53 mm
Type	SI
Weight	23 g
Thread	Left-hand thread
Lubrication	without
Packaging	1

contact@123bearing.ie

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE