

# SI Rod end SI20-ES-2RS-DURBAL - SI20-ES-2RS-DURBAL

<https://www.123bearing.ie/bearing-housing/rod-end/si/si20-es-2rs-durbal>

## SI20-ES-2RS



**female thread; lubrication required, according to DIN ISO 12240-4; series E**

**Description:** DIN ISO rod end E series. Made of spherical plain bearing DGE...E (ES) pressed into rod end body. Sliding combination steel / steel. Maintenance necessary. Bore diameter  $d \geq 15$  with grease nipple in rod end body and lubrication groove and hole in inner and outer ring. Bore diameter  $d \geq 15$  type DSI...ES-2RS with additional seals also available.

**Sliding combination:** steel / steel

**Inner ring:** bearing steel, hardened, ground and phosphated

**Outer ring:** bearing steel, hardened, ground and phosphated

**Lubrication:** lubrication required

**order number**

right hand thread	left hand thread	measurement (mm)						
d	G	B	C <sub>1</sub>	d <sub>2</sub>	d <sub>3</sub>	d <sub>4</sub>		
SI 20 ES (-2RS)		20	M 20 x 1.5	16	13,0	53	27,5	35

**measurement [mm]**

type	l <sub>3</sub> min	W	h	$\alpha$ [°]	load rating C <sub>0</sub> [kN]	weight [kg]
SI / SIL 20 ES (-2RS)	40	32	77	9	60,0	0,35

## PRODUCT FEATURES

Brand	DURBAL
N° Ean13	3663952497105
Inside diameter	20 mm
Outside diameter	53 mm
Thickness	16 mm
Type	SI
Weight	350 g
Thread	Right-hand thread
Lubrication	with
Packaging	1

[contact@123bearing.ie](mailto:contact@123bearing.ie)

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE