

SI Rod end SI25-ES-2RS-DURBAL - SI25-ES-2RS-DURBAL

<https://www.123bearing.ie/bearing-housing/rod-end/si/si25-es-2rs-durbal>

SI25-ES-2RS



female thread;
lubrication
required,
according to
DIN ISO 12240-4;
series E

Description: DIN ISO rod end E series. Made of spherical plain bearing DGL...E (ES) pressed into rod end body. Sliding combination steel / steel. Maintenance necessary. Bore diameter $d \geq 15$ with grease nipple in rod end body and lubrication groove and hole in inner and outer ring. Bore diameter $d \geq 15$ type DSI...ES-2RS with additional seals also available.

Sliding combination:
steel / steel

Inner ring:
bearing steel, hardened, ground and phosphated

Outer ring:
bearing steel, hardened, ground and phosphated

Lubrication:
lubrication required

Rod end body:
surface zinc plated

order number		measurement (mm)						
right hand thread	left hand thread	d	G	B	C1	d2	d3	d4
SI 25 ES (-2RS)		25	M 24 x 2	20	17,0	64	33,5	42

type	measurement [mm]			α [°]	load rating C_0 [kN]	weight [kg]
	l_1 min	W	h			
SI / SII 25 ES (-2RS)	48	36	94	7	83,0	0,64

PRODUCT FEATURES

Brand	DURBAL
N° Ean13	3663952497198
Inside diameter	25 mm
Inside diameter	0.984" inch
Outside diameter	64 mm
Outside diameter	2.52" inch
Thickness	20 mm
Thickness	0.787" inch
Type	SI
Weight	640 g
Thread	Right-hand thread
Lubrication	with
Packaging	1

contact@123bearing.ie

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE