

## SI Rod end SIL50-ES-DURBAL - SIL50-ES-DURBAL

<https://www.123bearing.ie/bearing-housing/rod-end/si/sil50-es-durbal>

### SIL50-ES



**female thread; lubrication required, according to DIN ISO 12240-4; series E**

**Description:** DIN ISO rod end E series. Made of spherical plain bearing DGE...E (ES) pressed into rod end body. Sliding combination steel / steel. Maintenance necessary. Bore diameter  $d \geq 15$  with grease nipple in rod end body and lubrication groove and hole in inner and outer ring. Bore diameter  $d \geq 15$  type DSI...ES-2/R5 with additional seals also available.

**Sliding combination:** steel / steel

**Inner ring:** bearing steel, hardened, ground and phosphated

**Outer ring:** bearing steel, hardened, ground and phosphated

**Lubrication:** lubrication required

**Rod end body:** surface zinc plated

order number		measurement [mm]						
right hand thread	left hand thread	d	G	B	C1	d2	d3	d4
SIL 50 ES		50	M 45 x 3	35	30,0	112	62,0	75

type	measurement [mm]			load rating $C_0$ [kN]	weight [kg]
	$l_1$ min	W	h		
SI / SIL 50 ES	68	65	160	290,0	3,5

## PRODUCT FEATURES

Brand	DURBAL
N° Ean13	3663952497587
Inside diameter	50 mm
Outside diameter	112 mm
Thickness	35 mm
Type	SI
Weight	3500 g
Thread	Left-hand thread
Lubrication	with
Packaging	1

[contact@123bearing.ie](mailto:contact@123bearing.ie)

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE