

SI Rod end SI60-ES-2RS-DURBAL - SI60-ES-2RS-DURBAL

<https://www.123bearing.ie/bearing-housing/rod-end/si/si60-es-2rs-durbal>

SI60-ES-2RS



female thread;
lubrication
required,
according to
DIN ISO 12240-4;
series E

Description: DIN ISO rod end E series. Made of spherical plain bearing DGE...E (ES) pressed into rod end body. Sliding combination steel / steel. Maintenance necessary. Bore diameter $d \geq 15$ with grease nipple in rod end body and lubrication groove and hole in inner and outer ring. Bore diameter $d \geq 15$ type DSI...ES-2RS with additional seals also available.

Sliding combination:
steel / steel

Inner ring:
bearing steel, hardened, ground and phosphated

Outer ring:
bearing steel, hardened, ground and phosphated

Lubrication:
lubrication required

order number
right hand thread left hand thread

SI 60 ES (-2RS)	d	G	measurement (mm)			
			B	C ₁	d ₂	d ₄
	60	M 52 x 3	44	38,0	135	70,0 88

measurement [mm]

type	l ₁ min	measurement [mm]			α [°]	load rating C ₀ [kN]	weight [kg]
		W	h				
SI / SII 60 ES (-2RS)	70	75	175	6	450,0	5,5	

PRODUCT FEATURES

Brand	DURBAL
N° Ean13	3663952497679
Inside diameter	60 mm
Outside diameter	135 mm
Thickness	44 mm
Type	-
Weight	5500 g
Thread	-
Lubrication	-
Packaging	-
Standard	-

contact@123bearing.ie

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE