

SI Rod end SI80-ES-DURBAL - SI80-ES-DURBAL

<https://www.123bearing.ie/bearing-housing/rod-end/si/si80-es-durbal>

SI80-ES



female thread; lubrication required, according to DIN ISO 12240-4; series E

Description: DIN ISO rod end E series. Made of spherical plain bearing DGL...E (ES) pressed into rod end body. Sliding combination steel / steel. Maintenance necessary. Bore diameter $d \geq 15$ with grease nipple in rod end body and lubrication groove and hole in inner and outer ring. Bore diameter $d \geq 15$ type DSI...ES-2/R5 with additional seals also available.

Sliding combination: steel / steel

Inner ring: bearing steel, hardened, ground and phosphated

Outer ring: bearing steel, hardened, ground and phosphated

Lubrication: lubrication required

Rod end body: surface zinc plated

order number		measurement (mm)									
right hand thread	left hand thread	d	G	B	C1	d2	d3	d4	h	W	l1 min
SI 80 ES		80	M 64 x 4	55	47,0	180	95,0	110			

type	measurement [mm]			α [°]	load rating C_0 [kN]	weight [kg]
	l_1 min	W	h			
SI / SIL 80 ES	85	100	230	6	750,0	12,0

PRODUCT FEATURES

Brand	DURBAL
N° Ean13	3663952497792
Inside diameter	80 mm
Inside diameter	3.15" inch
Outside diameter	180 mm
Outside diameter	7.087" inch
Thickness	55 mm
Thickness	2.165" inch
Type	SI
Weight	12000 g
Thread	Right-hand thread
Lubrication	with
Packaging	1

contact@123bearing.ie

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE