

SA Rod end SA40-ES-2RS-DURBAL - SA40-ES-2RS-DURBAL

<https://www.123bearing.ie/bearing-housing/rod-end/sa/sa40-es-2rs-durbal>

SA40-ES-2RS



**male thread:
lubrication
is necessary,
according to
DIN ISO 12240-4,
series E**

Description: DIN ISO rod end E series. Made of spherical plain bearing DGE...E (ES) pressed into rod end body. Sliding combination steel / steel. Maintenance necessary. Bore diameter $d \geq 15$ with grease nipple in rod end body and lubrication groove and hole in inner and outer ring. Bore diameter $d \geq 15$ type DSA...ES-2RS with additional seals also available.

**Ball end body:
surface zinc plated**

**Sliding combination:
steel / steel**

**Inner ring:
bearing steel, hardened, ground and phosphated**

**Outer ring:
bearing steel, hardened, ground and phosphated**

**Lubrication:
lubrication is necessary**

order number		measurement [mm]				
right hand thread	left hand thread	d	G	B	C ₁	d ₂
SA 40 ES (-2RS)		40	M 39 x 3	28	23,0	92

type	measurement [mm]			n [°]	load rating C ₀ [kN]	weight [kg]
	l ₁ min	l ₂	h			
SA / SAL 40 ES (-2RS)	86	46	150	7	180,0	1,800

PRODUCT FEATURES

Brand	DURBAL
N° Ean13	3663952498508
Inside diameter	40 mm
Outside diameter	92 mm
Thickness	28 mm
Type	SA
Weight	1800 g
Thread	Right-hand thread
Lubrication	with
Packaging	1

contact@123bearing.ie

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE