

TAPR Rod end GIHO-KL-60DO-DURBAL - GIHO-KL-60DO-DURBAL

<https://www.123bearing.ie/bearing-housing/rod-end/tapr/giho-kl-60do-durbal>

GIHO-KL-60DO



Description: Hydraulic rod end with slot and clamping arrangement. Made of spherical plain bearing DGE- ES pressed into rod end housing. Sliding combination steel/ steel with grease nipple.

Female thread: hydraulic rod ends, according to DIN 24555

Sliding combination: steel / steel

Inner ring: bearing steel, hardened, ground and phosphated

Outer ring: bearing steel, hardened, ground and phosphated

Lubrication: lubrication required

* without grease nipple

order number		measurement [mm]									
right hand thread	left hand thread	d	d ₁	d ₂	G	d ₄	d ₅	B	C ₁	C ₂	
GIHO-KL 60 DO		60	66,8	160	M 42 x 2	68	134	44	38	38	

type	measurement [mm]				α [°]	load rating C ₀ [kN]	weight [kg]
	h ₁	l ₁	l ₂	l ₃			
GIHN-K / GIHN-KL 60 DO	150	57	230,0	68	6	380,0	7,15

PRODUCT FEATURES

Brand	DURBAL
N° Ean13	3663952500881
Inside diameter	60 mm
Outside diameter	160 mm
Thickness	38 mm
Type	TAPR
Weight	7150 g
Thread	Left-hand thread
Lubrication	with
Packaging	1

contact@123bearing.ie

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE