

TPN Rod end GK60-DO-DURBAL - DGK60-DO-DURBAL


<https://www.123bearing.ie/bearing-housing/rod-end/tpn/dgk60-do-durbal>

GK60-DO



Description: DIN ISO Hydraulic rod end with welding slope and dowel pin at the end of rod. Made of spherical plain bearing DGE... ES (ES-2RS) pressed into rod end housing. Sliding combination steel / steel.
Type DGK...DO-2RS with two additional seals available on request with grease nipple.

hydraulic rod ends, according to DIN ISO 12240-4, series E



Sliding combination: steel / steel

Inner ring: bearing steel, hardened, ground and phosphated

Outer ring: bearing steel, hardened, ground and phosphated

Lubrication: lubrication required

* without grease nipple
** with grease nipple

order number	d	d ₁	d ₂	measurement [mm]			B	C ₁
GK 60 DO	60	66,8	135	6	70,0	44	38	

type	h ₁	l ₁	measurement [mm]		D	d ₁	α	load rating	weight
			l ₁	l ₂			[°]	C ₀ [kN]	[kg]
GK 60 DO	100	167,5	72,5	4,0	90	80,0	6	390,0	3,900

PRODUCT FEATURES

Brand	DURBAL
N° Ean13	3663952501499
Inside diameter	60 mm
Outside diameter	135 mm
Thickness	44 mm
Type	TPN
Weight	3900 g
Lubrication	with
Packaging	-
Standard	No standard

contact@123bearing.ie

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE