

SA Rod end BRM16-00-501-DURBAL - BRM16-00-501-DURBAL

<https://www.123bearing.ie/bearing-housing/rod-end/sa/brm16-00-501-durbal>

BRM16-00-501



male thread:
long-term lubrication, low maintenance, shields, adapter sizes according to DIN ISO 12240-4, series K

DURBAL® heavy-duty rod ends with integral self-aligning ball bearing

rod end housing:
forged steel, case-hardened bearing race, superfinished, rolled thread, surface galvanized, free of Cr VI

inner ring:
self-bearing steel, hardened, superfinished

lubrication:
aluminum-complex-soap-grease, temperature range -45 °C to +120 °C, approval according to USDA H1

lubrication fitting:
DIN 2455 D1/A (sizes 6 to 10)
DIN 21 412 H1 (sizes 12 to 30)

bearing clearance:
10 - 30 µm radial

tolerances:
see page 10

order number		measurements [mm]									
Type	right-hand thread	M 16	d ₁	d ₂	d ₃	d ₄	d ₅	l ₁	l ₂	l ₃	h
BRM 16 -00 -501			16	M 16		19,0	42	21	15,0		66
measurements [mm]		weight	calculation-factors		rotational speed limit	basic load rating					
Type	l	l ₃	α [°]	Y	v ₀	C	C ₀	dyn. [N]	stat. [N]		
BRM 16	40	22	8,0			975	6250	2350			

PRODUCT FEATURES

Brand	DURBAL
N° Ean13	3663952507033
Inside diameter	16 mm
Outside diameter	42 mm
Thickness	21 mm
Type	SA
Weight	190 g
Thread	Right-hand thread
Lubrication	with
Packaging	-
Standard	No standard

contact@123bearing.ie

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE