

# SI Rod end BRF20-60-501-DURBAL - BRF20-60-501-DURBAL

<https://www.123bearing.ie/bearing-housing/rod-end/si/brf20-60-501-durbal>

## BRF20-60-501



**rod end housing:**  
stainless steel 1.4534, hardened, bearing race superfinished

**inner ring:**  
stainless steel, hardened, surface superfinished

**lubrication:**  
aluminium-complex soap-grease, temperature range: -45 °C to +120 °C, approval according to USDA H1

**lubrication fitting:**  
DIN 3405 D1/A (sizes 6 to 10)  
DIN 71 412 H1 (sizes 12 to 20)

**bearing clearance:**  
10 - 30 µm radial

**tolerances:**  
see page 10

**DURBAL® heavy-duty rod ends with integral self-aligning ball bearing in stainless steel**

**female thread:**  
long-term lubrication, low maintenance, shields, adapter sizes according to DIN ISO 12240-4, series K

order number		measurements [mm]											
type	right-hand thread	d <sub>1</sub>	d <sub>2</sub>	d <sub>3</sub>	d <sub>4</sub>	d <sub>5</sub>	d <sub>6</sub>	d <sub>7</sub>	b <sub>1</sub>	b <sub>2</sub>	h		
BRF 20 -60 -501		20	27,5	M 20 x 1,5	24,5	50	34	25	18,0	77			
measurements [mm]		weight		calculation-factors	rotational speed limit	basic load rating							
type	l <sub>1</sub>	l <sub>2</sub>	SW	α [°]	Y	v <sub>0</sub>	speed limit [min]	d <sub>yn.</sub> C [N]	stat. C <sub>0</sub> [N]				
BRF 20	33	10,0	26	30	7,0	0,367	2,46	2,58	825	5350	2300		

## PRODUCT FEATURES

Brand	DURBAL
N° Ean13	3663952509310
Inside diameter	20 mm
Outside diameter	50 mm
Thickness	25 mm
Type	SI
Weight	367 g
Thread	Right-hand thread
Lubrication	with
Packaging	1

[contact@123bearing.ie](mailto:contact@123bearing.ie)

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE