

SI Rod end

BRF1-1-00-501-DURBAL - BRF1-1-00-501-DURBAL

<https://www.123bearing.ie/bearing-housing/rod-end/si/brf1-1-00-501-durbal>

BRF1/1-00-501

rod end housing:
forged steel, case-hardened bearing race, superfinished, surface galvanized, free of Cr VI

inner ring:
ball bearing steel, hardened, superfinished

lubrication:
aluminum complex soap-grease, temperature range -45 °C to +120 °C, approval according to USDA H1

lubrication fitting:
DIN 3405 D1/A (sizes 1/4 and 3/8)
DIN 71 412 H1 (sizes 1/2 and 1 1/4)

bearing clearance:
10 - 30 µm radial

tolerances:
see page 10

DURBAL® heavy-duty rod ends with integral self-aligning ball bearing

female thread:
long-term lubrication, low maintenance, shields, dimensions in inches

order number		measurements [inches]										
type	right hand thread	left hand thread	d1	d2	d3	d4	d5	d6	d7	b1	b3	
BRF 1/1 -00	-501		1.000	1.171	1.0000-12 UNF	1.161	2.519	1.377	1.220	.866		
measurements [inches]		weight	calculation factors	rotational speed limit	basic load rating	stat.						
type	h	l	l1	l2	SW	α [°]	Y	%	rpm	C	C0	
BRF 1/1	3.720	1.653	.236	1.279	1.181	5.0	0.570	2.02	2.12	600	11030	5680

PRODUCT FEATURES

Brand	DURBAL
N° Ean13	3663952510217
Inside diameter	25.4 mm
Inside diameter	1" inch
Outside diameter	63.98 mm
Outside diameter	2.519" inch
Thickness	30.99 mm
Thickness	1.22" inch
Type	SI
Weight	570 g
Thread	Right-hand thread
Lubrication	with
Packaging	1

contact@123bearing.ie
 +33 359 36 04 90
 CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE