

Deep groove ball bearing single row 1640-DC-NICE - 1640-DC-NICE

<https://www.123bearing.ie/bearing-housing/deep-groove-bearing/single-row/1640-dc-nice>

1600 Series™ Precision Ground Radial Bearings (con't) **NICE**



SUFFIX						PRINCIPLE DIMENSIONS	
BEARING	DOUBLE SEAL	SINGLE SEAL	DOUBLE SHIELD	SINGLE SHIELD	OPEN	BORE d (in) (mm)	O.D. D (in) (mm)
1640™	DC					+0.000 +0.000 -0.005 -0.013	+0.000 +0.000 -0.005 -0.013
						0.9750 22.225	2.0000 50.800

BASIC LOAD RATINGS			WEIGHT	ABUTMENT AND FILLET DIMENSIONS		
WIDTH B (in) (mm)	DYNAMIC C (lbf) (N)	STATIC C ₀ (lbf) (N)	W ⁰ (kg)	d _a min (in) (mm)	D _a max (in) (mm)	r max (in) (mm)
0.5625 14.288	2967 13203	1350 6008	0.29 0.13	1.113 28.27	1.780 44.70	0.035 0.89

ⓘ Weights given are for greased and sealed versions
Ⓜ 1638 and larger +0.000/-0.006 (-0.000/-0.15)

PRODUCT FEATURES

Brand	NICE
N° Ean13	637400291839
Inside diameter	22.225 mm
Outside diameter	50.8 mm
Thickness	14.288 mm
Weight	130 g
Packaging	1

contact@123bearing.ie

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE