


## Deep groove ball bearing single row 400-21V-NICE - 400-21V-NICE

<https://www.123bearing.ie/bearing-housing/deep-groove-bearing/single-row/400-21v-nice>

**400 Series® Single Row. Unground Radial Bearings** **NICE®**

- RADIAL UNGROUND BEARING
- EASY TO USE INCH DIMENSIONS
- MODERATE LOADS
- MAX SPEED RANGE - 1000 - 1200 RPM
- HARDENED RINGS
- FULL COMPLIMENT OF BALLS
- FULLY UNITIZED ASSEMBLY
- BEARING SUPPLIED PRE-GREASED STANDARD



BEARING	SUFFIX	BEARING DIMENSIONAL DATA				BALLS	
		A BORE (in) (mm)	B O.D. (in) (mm)	C WIDTH (in) (mm)	D WIDTH (in) (mm)	No.	Size
400™	21V	0.437 11.20	1.125 28.58	0.375 9.53	0.375 9.53	18	1/8 3.18

WEIGHT W (lbs) (kg)	RADIAL CAPACITY					
	REVOLUTIONS PER MINUTE					
	50	100	200	300	600	1200
	(lbs)	(lbs)	(lbs)	(lbs)	(lbs)	(lbs)
	(N)	(N)	(N)	(N)	(N)	(N)
0.07	200	139	96	78	54	38
0.03	890	619	427	347	240	168

Notes  
Balls - Carbon Steel Grade 200      Bands - 1010 Carbon Steel, Soft  
Rings - Carbon Steel, Case Hardened      Bearings supplied prelubricated with grease

### PRODUCT FEATURES

Brand	NICE
N° Ean13	3663952560052
Inside diameter	11.1 mm
Outside diameter	28.58 mm
Thickness	9.53 mm
Weight	30 g
Packaging	1

[contact@123bearing.ie](mailto:contact@123bearing.ie)

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE