



SI Rod end

AL-SA-019-DUNLOP - AL-SA-019-DUNLOP

<https://www.123bearing.ie/bearing-housing/rod-end/si/al-sa-019-dunlop>

FEMALE ROD ENDS

Housing: Aluminum A6061, Black Anodized

AL SERIES

Description:
AL-Series is our 3-piece aluminum light weight range of self-lubricating general purpose female rod ends suitable for light industrial/mechanical load applications requiring low friction, with good wear resistance and available in metric bore and thread sizes. They have excellent moisture resistance and require no maintenance.

Material Specifications:
Housing: Aluminum A6061, black anodized. Race: GR-nylon LV-3H. Ball: Bearing steel 100Cr6, case hardened and electroless nickel plated.

Features Metric bore & thread sizes Low friction Self-lubricating Good wear resistance Excellent moisture resistance No maintenance Light weight	Possible Applications Light industrial/mechanical applications Weight restricted applications Linear movement sensors	Temperature Range -30°C to +170°C Specification ELV & RoHS compliant
--	---	---

Part No. Right Hand	Part No. Left Hand	Bore Size	Thread	W	H	D	L1	L2	O	AF	Static Load Rating Radial (Newtons)
AL-SA-019		5	M5x0.80	8	8.00	16	18.0	6.5	9.0	9.0	5,340

PRODUCT FEATURES

Brand	DUNLOP
N° Ean13	3616060556455
Inside diameter	5 mm
Outside diameter	8 mm
Thickness	6 mm
Type	SI
Thread	Right-hand thread
Lubrication	with
Packaging	1
Standard	No standard

contact@123bearing.ie
+33 359 36 04 90
CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE