


SI Rod end AL-SA-082-LH-DUNLOP - AL-SA-082-LH-DUNLOP

<https://www.123bearing.ie/bearing-housing/rod-end/si/al-sa-082-lh-dunlop>

FEMALE ROD ENDS DUNLOP

Housing: Aluminum A6061, Black Anodized

AL SERIES

Description:
AL-Series is our 3-piece aluminum light weight range of self-lubricating general purpose female rod ends suitable for light industrial/mechanical load applications requiring low friction, with good wear resistance and available in metric bore and thread sizes. They have excellent moisture resistance and require no maintenance.

Material Specifications:
Housing: Aluminum A6061, black anodized. Race: GR-nylon LV-3H. Ball: Bearing steel 100Cr6, case hardened and electroless nickel plated.

Features

- Metric bore & thread sizes
- Low friction
- Self-lubricating
- Good wear resistance
- Excellent moisture resistance
- No maintenance
- Light weight

Possible Applications

- Light industrial/mechanical applications
- Weight restricted applications
- Linear movement sensors

Temperature Range

-30°C to +170°C

Specification

ELV & RoHS compliant

Part No. Right Hand	Part No. Left Hand	Bore Size	Thread	W	H	D	L1	L2	O	AF	Static Load Rating Radial (Newtons)
AL-SA-082LH		8	M8x1.25	12	9.00	22	36.0	16.0	10.4	14.0	7,720

PRODUCT FEATURES

Brand	DUNLOP
N° Ean13	3616060556547
Inside diameter	8 mm
Outside diameter	12 mm
Thickness	9 mm
Type	SI
Thread	Right-hand thread
Lubrication	with
Packaging	1

contact@123bearing.ie

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE