


# GE Rod end GE304-ES-2RS-DUNLOP - GE304-ES-2RS-DUNLOP

<https://www.123bearing.ie/bearing-housing/rod-end/ge/ge304-es-2rs-dunlop>

**SPHERICAL BEARINGS** **DUNLOP**

**GEZ ES SERIES**

**Description:**  
GEZ-ES-Series is our 2-piece fractured outer ring metric range of spherical plain bearings used in non rotational applications. Ball and race sliding surfaces are treated with MoS<sub>2</sub> for increased lubricity on wear surface. A lubrication groove is provided on the raceway for applications requiring re-lubrication after installation.

**Material Specifications:**  
Outer ring: Bearing steel 100Cr6, case hardened and manganese phosphated, treated with MoS<sub>2</sub>. Ball: Bearing steel 100Cr6, case hardened and manganese phosphated. Seals: Polyurethane.

**Features:**  
Metric bore sizes  
Low cost  
Maintenance required  
Up to 140mm bore sizes available

**Possible Applications:**  
Light to heavy industrial/mechanical applications  
Construction equipment  
Agricultural equipment  
Hydraulic applications

**Temperature Range:**  
-34°C to +121°C

**Specifications:**  
ELV & RoHS compliant

**Outer Ring:** Bearing Steel 100Cr6, Case Hardened and Manganese Phosphate, wear faces treated with MoS<sub>2</sub>.

**Balls:** Bearing Steel 100Cr6, Case Hardened and Manganese Phosphate

**Seals:** Polyurethane

Part No. Unsealed	Part No. Sealed	Bore Size	W	H	D	Static Load Rating (Newtons) Radial
	GEZ304ES-2RS	3-1/4	72.238	61.902	130.175	1,760,000

## PRODUCT FEATURES

Brand	DUNLOP
N° Ean13	3616060558336
Inside diameter	82.55 mm
Outside diameter	130.175 mm
Thickness	72.23 mm
Type	GE
Thread	Right-hand thread
Lubrication	with
Packaging	1

[contact@123bearing.ie](mailto:contact@123bearing.ie)

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE