

## Drawn cup roller bearing BA1716-Z-IKO - BA1716-Z-IKO

<https://www.123bearing.ie/bearing-housing/needle-roller-bearing/drawn-cup/ba1716-z-iko>



Boundary dimensions mm(inch)			Standard mounting dimensions mm				Basic dynamic load rating	Basic static load rating	Allowable rotational speed	Assemblies	
<i>F<sub>w</sub></i>	<i>D</i>	<i>C</i>	<i>l<sub>2</sub></i>	<i>h<sub>6</sub></i>	<i>J<sub>7</sub></i>	<i>C</i>	<i>CF</i>	rpm	inner ring		
26.988 (1)	33.338 (1 1/16)	25.401 (1.000)	2.0	Max.	Min.	Max.	Min.	N	N		
								20000	38300	14000	—

### PRODUCT FEATURES

Brand	IKO
N° Ean13	3616060601230
Inside diameter	26.988 mm
Outside diameter	33.338 mm
Thickness	25.4 mm
Limiting speed	14000 rpm
Dynamic load	20 kN
Static load	38.3 kN
Packaging	1

[contact@123bearing.ie](mailto:contact@123bearing.ie)

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE