


Tapered roller bearing 2559-2525-TIMKEN - 2559-2525-TIMKEN

<https://www.123bearing.ie/bearing-housing/roller-bearing/tapered/2559-2525-timken>

TYPE TS



Dimensions		Abutment and Fit Dimensions	
d - Bore	30.163 mm 1.1875 in	k - Case Backface To Case Face	0.762 mm 0.030 in
D - Cup Outer Diameter	72.022 mm 2.8351 in	r - Cup Backface To Case Face	0.75 mm 0.030 in
B - Cone Width	25.267 mm 0.9943 in	d_1 - Cup Frontface Backing Diameter	36.46 mm 1.434 in
C - Cup Width	19.050 mm 0.7500 in	d_2 - Cup Backface Backing Diameter	27.06 mm 1.066 in
T - Bearing Width	23.813 mm 0.9375 in	d_3 - Cup Frontface Backing Diameter	66.02 mm 2.601 in
Basic Load Ratings		d_4 - Cup Backface Backing Diameter	62.99 mm 2.48 in
C_{90} - Dynamic Radial Rating (90 million revolutions) ¹	4850 lbf 21 780 N	Ab - Cage Case Frontface Clearance	1.5 mm 0.059 in
C_3 - Dynamic Radial Rating (3 million revolutions) ²	18462 lbf 82700 N	Aa - Cage Cone Backface Clearance	0.5 mm 0.02 in
C_0 - Static Radial Rating	31300 lbf 14000 N	a - Effective Center Location ³	0.5 mm 0.02 in
C_{app} - Dynamic Thrust Rating (90 Million revolutions) ⁴	2280 lbf 10200 N		
Factors			
K - Factor ⁵	2.54		
ν - ISO Factor ⁶	0.27		
γ - ISO Factor ⁶	2.19		
C_1 - Heat Generation Factor (Steady Rotation)	23.6		
C_2 - Heat Generation Factor (300 Revs/Min)	8.6		
C_3 - Geometry Factor	0.0676		

PRODUCT FEATURES

Brand	TIMKEN
N° Ean13	3616060668097
Inside diameter	30.163 mm
Outside diameter	72.022 mm
Thickness	23.813 mm
Packaging	1

contact@123bearing.ie

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE