

Glue

609-50ML-LOCTITE - 609-50ML-LOCTITE

<https://www.123bearing.ie/lubricant-adhesive/lubricant/glue/609-50ml-loctite>

TITRE	Anaérobie
DESCRIPTION	Solidement ML/ASTM, viscosité faible
NOM	LOCTITE 609
CONDITIONNEMENT	31 30ml
APPROBATION*	

Description

LOCTITE® 609 is a green, high strength methacrylate ester acrylic retaining compound designed for the bonding of cylindrical fitting parts. The product cures in the absence of air between close fitting metal surfaces. Typical applications include rotor to shafts in fractional and subfractional horsepower motors. Locks bushings and sleeves in housings on shafts. Augments press fits.

Avantages

Low viscosity
Prevents loosening and leakage from shock and vibration
Augments press fits
Tested to the lot requirements of Military Specification MIL-R-46082B (this is a regional approval)

Caractéristiques

High strength methacrylate ester acrylic retaining compound designed for the bonding of cylindrical fitting parts.



PRODUCT FEATURES

Brand	LOCTITE
N° Ean13	4058093028117
Type	FIXATION ROULEMENT
Weight	83 g
Packaging	1
Use	Anaérobie

contact@123bearing.ie

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE