

Lubricant

LB-8154-400ML-LOCTITE - LB-8154-400ML-LOCTITE

<https://www.123bearing.ie/lubricant-adhesive/lubricant/lubricant/lb-8154-400ml-loctite>

TYPE	Lubrifiant
DESCRIPTION	Anti-Seize MoS2 multi-usages (ex PA 450), grade alimentaire
NOUVEAU NOM BRANDING	LOCTITE LB 8154
CONDITIONNEMENT	Aé-400 ml
DANGEROUS GOOD	Yes
COMMENTAIRE	-
APPROBATION*	NSF

Description

Lubrifiant LOCTITE 8154 - Anti-Seize, pâte/aérosol de montage au MoS2

Les avantages

Pâte de montage au MoS2
Facilite le montage et le démontage des pièces cylindriques
Supporte des conditions de fonctionnement extrêmes
Librifie et étanche les pièces cylindriques, les roulements et les roues d'engrenage à vitesse faible
Conforme à la norme NSF, catégorie H2, n° 122982

Fiche technique

Couleur : noir
Plage de températures de service : -30 °C à +150 °C
Conditionnement : aérosol de 400 ml

Avantages

Registered to NSF Category H2 for use as a lubricant where there is no possibility of food contact in and around food processing areas.
Prevents fretting and wear
Protects components during the running in periods and it assures easy disassembly after severe working conditions at temperatures up to +450°C

Caractéristiques

Black oil spray lubricant anti-seize based on mineral oil, lithium soap and MoS₂, using propane/butane as a propellant.

PRODUCT FEATURES

Brand	LOCTITE
N° Ean13	5010266264820
Weight	358 g
Packaging	1

contact@123bearing.ie

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE