


Needle roller bearing NKX40-ZA-INA - NKX40-ZA-INA

<https://www.123bearing.ie/bearing-housing/needle-roller-bearing/needle/nkx40-za-ina>



F_w	40 mm
D	52 mm
C	32 mm Tolérance: -0,25
C_1	13 mm Tolérance: -0,2
C_2	10 mm
D_{2max}	61,2 mm
d_w	55,7 mm
d_w	40 mm Tolérance: E8
$f_a max$	0,6 mm
f_{max}	0,6 mm
	NKX40Z désignation selon DIN 5429
m	208 g masse
C_{10}	29500 N charge dyn. de base, radiale
C_{0r}	47000 N charge statique de base, radiale
C_{10}	27000 N charge dyn. de base, axiale
C_{0a}	63000 N charge statique de base, axiale
C_{10}	8300 N charge limite radiale à la fatigue
C_{10a}	3000 N charge limite axiale à la fatigue
n_0	4000 1/min vitesse limite
	IR35X40X20 bague intérieure utilisable

PRODUCT FEATURES

Brand	INA
N° Ean13	3663952127903
Inside diameter	40 mm
Outside diameter	52 mm
Thickness	32 mm
Packaging	1

contact@123bearing.ie

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE