

Housed bearing 2 bolts P2BC-40M-CPSS-DFH-SKF - P2BC-40M-CPSS-DFH-SKF

<https://www.123bearing.ie/bearing-housing/housed-bearing/cast-iron-housed-bearing-2/p2bc-40m-cpss-dfh-skf>

| Données de calcul | |
|--------------------------|----------------------------------|
| Charge dynamique de base | C 24.7 kN |
| Charge statique de base | C ₀ 19 kN |
| Limite de fatigue | P ₀ 0.8 kN |
| Compliance with standard | Not standardized |
| Matériau | Compatible for the SKF Food Line |
| Sealing solution | Gutter seals |
| Dimensions | |
| d | 40 mm |
| A | 44 mm |
| A ₁ | 44 mm |
| A ₂ | 79.9 mm |
| B | 40.7 mm |
| W | 12 mm |
| H | 38.2 mm |
| H ₁ | 49.2 mm |
| H ₂ | 20 mm |
| J | 137 mm |
| J | max. 140 mm |
| J | min. 134 mm |
| L | 179 mm |
| N | 17 mm |
| N ₁ | 14 mm |
| N ₂ | 30.2 mm |
| Plots de centrage | |
| G | 12 mm |
| G | 6.6 in |
| Calculation data | |
| Limiting speed | 900 v/min |
| with shaft tolerance H8 | |

PRODUCT FEATURES

| | |
|--------------------------|--------------------------|
| Brand | SKF |
| N° Ean13 | 7316577859327 |
| Shaft diameter | 40 mm |
| No. of fasteners | 2 |
| Tightening | Eccentric locking ring |
| Mounting center distance | 137 mm |
| Material | FOOD-GRADE POLYPROPYLENE |
| Packaging | 1 |

contact@123bearing.ie

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE