

Tapered roller bearing T2CC022-JTEKT - T2CC022-JTEKT

<https://www.123bearing.ie/bearing-housing/roller-bearing/tapered/t2cc022-jtekt>

Single-row tapered roller bearings
metric series

Koyo



| Boundary dimensions (mm) | | | | | Basic load ratings (kN) | | | | Limiting speeds (min ⁻¹) | | Bearing No. ¹⁾ |
|--------------------------|----|----|------|------|-------------------------|-----------------|-----------------|------------------|--------------------------------------|----------|---------------------------|
| d | D | T | B | C | C _r | C _{0r} | C ₉₀ | C ₁₀₀ | Grease lub. | Oil lub. | |
| 22 | 47 | 17 | 17.5 | 13.5 | 1 | 1 | 32.7 | 35.9 | 8 700 | 12 000 | T2CC022 |

| Dimension series to ISO 955 (Refer. 1) | Load center (mm) a | Mounting dimensions (mm) | | | | | | | | Constant e | Axial load factors | | (Refer. 1) Mass (kg) | |
|----------------------------------------|--------------------|--------------------------|----------------------|----------------------|----------------------|----------------------|----------------------|----------------------|----------------------|------------|--------------------|----------------|----------------------|-------|
| | | d _{1a} min. | d _{1a} max. | D _{1a} min. | D _{1a} max. | S _{1a} min. | S _{1a} max. | r _{1a} min. | r _{1a} max. | | Y ₁ | Y ₀ | | |
| 2CC | 11.3 | 27.5 | 28 | 41.5 | 40 | 44 | 4 | 3.5 | 1 | 1 | 0.33 | 1.79 | 0.99 | 0.138 |

PRODUCT FEATURES

| | |
|------------------|---------------|
| Brand | JTEKT |
| N° Ean13 | 3663952400419 |
| Inside diameter | 22 mm |
| Outside diameter | 47 mm |
| Thickness | 17 mm |
| Packaging | 1 |

contact@123bearing.ie

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE