

Tapered roller bearing 302-32-R-JTEKT - 302-32-R-JTEKT

<https://www.123bearing.ie/bearing-housing/roller-bearing/tapered/302-32-r-jtekt>

Single-row tapered roller bearings
metric series

Koyo



Boundary dimensions (mm)					Basic load ratings (kN)				Limiting speeds (min ⁻¹)		Bearing No. ¹⁾			
d	D	T	B	C	C _r	C _{0r}	C ₉₀	C ₁₀₀	Grease lub.	Oil lub.				
32	65	18.25	17	15	1	1	48.0	51.4	6 200	8 200	302/32R			
Dimension series to ISO 955 (Refer. 1)	Load center (mm) a	Mounting dimensions (mm)								Constant e	Axial load factors		(Refer. 1) Mass (kg)	
		d _{1a} min.	d _{1a} max.	D _{1a} min.	D _{1a} max.	S _{1a} min.	S _{1a} max.	r _{1a} min.	r _{1a} max.		Y ₁	Y ₀		
—	14.9	37.5	39	59.5	55	61	3	3	1	1	0.37	1.60	0.88	0.266

PRODUCT FEATURES

Brand	JTEKT
N° Ean13	3663952400785
Inside diameter	32 mm
Outside diameter	65 mm
Thickness	18.25 mm
Packaging	1

contact@123bearing.ie

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE