

Tapered roller bearing 30315-DR-JTEKT - 30315-DR-JTEKT

<https://www.123bearing.ie/bearing-housing/roller-bearing/tapered/30315-dr-jtekt>

Single-row tapered roller bearings
metric series

Koyo



Boundary dimensions (mm)				Basic load ratings (kN)				Limiting speeds (min ⁻¹)		Bearing No. ¹⁾				
d	D	T	B	C	C_r	C_{0r}	Grease lub.	Oil lub.						
75	160	40	37	28	222	266	2 100	2 900	30315DR					
Dimension series to ISO 995 (Refer. 1)	Load center (mm) a	Mounting dimensions (mm)								Constant e	Axial load factors		(Refer. 1) Mass (kg)	
		d_a min.	d_a max.	D_a min.	D_a max.	S_a min.	S_a max.	r_a min.	r_a max.		Y_1	Y_0		
—	48.8	89	91	148	127	151	6	14	2.5	2	0.81	0.74	0.41	3.48

PRODUCT FEATURES

Brand	JTEKT
N° Ean13	4549250122149
Inside diameter	75 mm
Outside diameter	160 mm
Thickness	40 mm
Weight	3516 g
Packaging	1

contact@123bearing.ie

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE