

## Tapered roller bearing 32317-JR-JTEKT - 32317-JR-JTEKT

<https://www.123bearing.ie/bearing-housing/roller-bearing/tapered/32317-jr-jtekt>

Single-row tapered roller bearings  
metric series

**Koyo**



Boundary dimensions (mm)					Basic load ratings (kN)				Limiting speeds (min <sup>-1</sup> )		Bearing No. <sup>1)</sup>
d	D	T	B	C	C <sub>r</sub>	C <sub>0r</sub>	Grease lub.	Oil lub.			
85	180	63.5	60	49	439	587	2 200	3 000	<b>32317JR</b>		

  

Dimension series to ISO 995 (Refer. 1)	Load center (mm) a	Mounting dimensions (mm)								Constant e	Axial load factors		(Refer. 1) Mass (kg)	
		d <sub>1a</sub> min.	d <sub>1a</sub> max.	D <sub>1a</sub> min.	D <sub>1a</sub> max.	S <sub>1a</sub> min.	S <sub>1a</sub> max.	r <sub>1a</sub> min.	r <sub>1a</sub> max.		Y <sub>1</sub>	Y <sub>0</sub>		
260	43.8	103	103	166	150	167	5	14.5	3	2.5	0.35	1.74	0.96	7.42

### PRODUCT FEATURES

Brand	JTEKT
N° Ean13	4549250125225
Inside diameter	85 mm
Inside diameter	3.346" inch
Outside diameter	180 mm
Outside diameter	7.087" inch
Thickness	63.5 mm
Thickness	2 1/2" inch
Packaging	1

[contact@123bearing.ie](mailto:contact@123bearing.ie)

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE