

Tapered roller bearing 30318-DJR-JTEKT - 30318-DJR-JTEKT

<https://www.123bearing.ie/bearing-housing/roller-bearing/tapered/30318-djr-jtekt>

Single-row tapered roller bearings
metric series

Koyo



Boundary dimensions (mm)				Basic load ratings (kN)		Limiting speeds (min ⁻¹)		Bearing No. ¹⁾						
d	D	T	B	C	C _r	C _{0r}	Grease lub.		Oil lub.					
90	190	46.5	43	30	288	350	1 700	2 400	30318DJR					
Dimension series to ISO355 (Refer.1)	Load center (mm) a	Mounting dimensions (mm)						Constant e	Axial load factors		(Refer.1) Mass (kg)			
		d _{1a} min.	d _{1a} max.	D _{1a} min.	D _{1a} max.	S _{1a} min.	S _{1a} max.		r _{3a} min.	r _{3a} max.		Y ₁	Y ₀	
7GB	59.6	108	109	176	151	179	6	16.5	3	2.5	0.83	0.73	0.40	5.57

PRODUCT FEATURES

Brand	JTEKT
N° Ean13	3663952409658
Inside diameter	90 mm
Outside diameter	190 mm
Thickness	46.5 mm
Packaging	1

contact@123bearing.ie

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE