

Tapered roller bearing 30319-JTEKT - 30319-JTEKT

<https://www.123bearing.ie/bearing-housing/roller-bearing/tapered/30319-jtekt>

Single-row tapered roller bearings
metric series

Koyo



Boundary dimensions (mm)				Basic load ratings (kN)				Limiting speeds (min ⁻¹)		Bearing No. ¹⁾				
d	D	T	B	C	C _r	C _{0r}	Grease lub.	Oil lub.						
95	200	49.5	45	38	4	3	317	368	2 000	2 600	30319			
Dimension series to ISO95 (Refer. 1)	Load center (mm) a	Mounting dimensions (mm)								Constant e	Axial load factors		(Refer. 1) Mass (kg)	
		d _{1a} min.	d _{1a} max.	d _{2a} min.	d _{2a} max.	S _{1a} min.	S _{1a} max.	r _{3a} min.	r _{3a} max.		Y ₁	Y ₀		
—	39.8	113	118	186	172	186	5	11.5	3	2.5	0.35	1.73	0.95	6.32

PRODUCT FEATURES

Brand	JTEKT
N° Ean13	4549250122354
Inside diameter	95 mm
Outside diameter	200 mm
Thickness	49.5 mm
Packaging	1

contact@123bearing.ie

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE