

Tapered roller bearing 30320-JTEKT - 30320-JTEKT

<https://www.123bearing.ie/bearing-housing/roller-bearing/tapered/30320-jtekt>

Single-row tapered roller bearings
metric series

Koyo



Boundary dimensions (mm)				Basic load ratings (kN)				Limiting speeds (min ⁻¹)		Bearing No. ¹⁾				
d	D	T	B	C	C _r	C _{0r}	Grease lub.	Oil lub.						
100	215	51.5	47	39	344	400	1 800	2 400	30320					
Dimension series to ISO 955 (Refer. 1)	Load center (mm) a	Mounting dimensions (mm)								Constant e	Axial load factors		(Refer. 1) Mass (kg)	
		d _{1a} min.	d _{1a} max.	D _{1a} min.	D _{1a} max.	S _{1a} min.	S _{1a} max.	r _{1a} min.	r _{1a} max.		Y ₁	Y ₀		
—	41.4	118	127	201	184	200	6	12.5	3	2.5	0.35	1.73	0.95	7.76

PRODUCT FEATURES

Brand	JTEKT
N° Ean13	4549250122408
Inside diameter	100 mm
Outside diameter	215 mm
Thickness	51.5 mm
Packaging	1

contact@123bearing.ie

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE