

Tapered roller bearing 30320-JR-JTEKT - 30320-JR-JTEKT

<https://www.123bearing.ie/bearing-housing/roller-bearing/tapered/30320-jr-jtekt>

Single-row tapered roller bearings
metric series

Koyo

Technical data

Boundary dimensions (mm)					Basic load ratings (kN)				Limiting speeds (min ⁻¹)		Bearing No.
<i>d</i>	<i>D</i>	<i>T</i>	<i>B</i>	<i>C</i>	<i>C₀</i>	<i>C_{0r}</i>	<i>C_r</i>	<i>C_{0r}</i>	Grease lub.	Oil lub.	
100	215	51.5	47	39	4	3	422	521	1 800	2 400	30320JR

Dimension series to ISO 955 (Refer. 1)	Load center (mm) <i>a</i>	Mounting dimensions (mm)										Constant <i>e</i>	Axial load factors		(Refer. 1) Mass (kg)
		<i>d_a</i> min.	<i>d_a</i> max.	<i>D_a</i> min.	<i>D_a</i> max.	<i>S_a</i> min.	<i>S_a</i> max.	<i>r_a</i> min.	<i>r_a</i> max.	<i>r_b</i> max.	<i>r_c</i> max.		<i>Y₁</i>	<i>Y₀</i>	
2GB	42.7	118	127	201	184	200	6	12.5	3	2.5	0.35	1.74	0.96	8.49	

PRODUCT FEATURES

Brand	JTEKT
N° Ean13	3663952410593
Inside diameter	100 mm
Outside diameter	215 mm
Thickness	51.5 mm
Packaging	1

contact@123bearing.ie

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE