

# Tapered roller bearing 32320-JR-JTEKT - 32320-JR-JTEKT

<https://www.123bearing.ie/bearing-housing/roller-bearing/tapered/32320-jr-jtekt>

Single-row tapered roller bearings  
metric series

Koyo



Boundary dimensions (mm)				Basic load ratings (kN)				Limiting speeds (min <sup>-1</sup> )		Bearing No. <sup>1)</sup>		
d	D	T	B	C	C <sub>r</sub>	C <sub>0r</sub>	Grease lub.	Oil lub.				
100	215	77.5	73	60	579	783	1 800	2 400	32320JR			
Dimension series to ISO 355 (Refer. 1)	Load center (mm) a	Mounting dimensions (mm)							Constant e	Axial load factors (Refer. 1)		Mass (kg)
26D	53.9	d <sub>1a</sub> min.	d <sub>2a</sub> max.	D <sub>1a</sub> max.	D <sub>2a</sub> min.	S <sub>1a</sub> min.	S <sub>2a</sub> min.	r <sub>1a</sub> max.	r <sub>2a</sub> max.	1.74	0.96	13.0

## PRODUCT FEATURES

Brand	JTEKT
N° Ean13	3663952410623
Inside diameter	100 mm
Outside diameter	215 mm
Thickness	77.5 mm
Packaging	1

[contact@123bearing.ie](mailto:contact@123bearing.ie)

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE