

## Tapered roller bearing 32321-JR-JTEKT - 32321-JR-JTEKT

<https://www.123bearing.ie/bearing-housing/roller-bearing/tapered/32321-jr-jtekt>

Single-row tapered roller bearings  
metric series

Koyo



Boundary dimensions (mm)					Basic load ratings (kN)				Limiting speeds (min <sup>-1</sup> )		Bearing No. <sup>1)</sup>
d	D	T	B	C	C <sub>r</sub>	C <sub>0r</sub>	C <sub>90</sub>	C <sub>100</sub>	Grease lub.	Oil lub.	
105	225	81.5	77	63	635	866	1 800	2 300			32321JR

  

Dimension series to ISO 355 (Refer.)	Load center (mm) a	Mounting dimensions (mm)								Constant e	Axial load factors		(Refer.) Mass (kg)	
		d <sub>1a</sub> min.	d <sub>1a</sub> max.	D <sub>1a</sub> min.	D <sub>1a</sub> max.	S <sub>1a</sub> min.	S <sub>1a</sub> max.	r <sub>1a</sub> min.	r <sub>1a</sub> max.		Y <sub>1</sub>	Y <sub>0</sub>		
260	56.1	123	128	211	185	209	8	18.5	3	2.5	0.35	1.74	0.96	14.9

### PRODUCT FEATURES

Brand	JTEKT
N° Ean13	3663952411217
Inside diameter	105 mm
Inside diameter	4.134" inch
Outside diameter	225 mm
Outside diameter	8.858" inch
Thickness	81.5 mm
Thickness	3.209" inch
Packaging	1

[contact@123bearing.ie](mailto:contact@123bearing.ie)

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE