

# Tapered roller bearing 31322-JR-JTEKT - 31322-JR-JTEKT

<https://www.123bearing.ie/bearing-housing/roller-bearing/tapered/31322-jr-jtekt>

Single-row tapered roller bearings  
metric series

Koyo



Boundary dimensions (mm)					Basic load ratings (kN)				Limiting speeds (min <sup>-1</sup> )		Bearing No. <sup>1)</sup>			
d	D	T	B	C	C <sub>r</sub>	C <sub>0r</sub>	C <sub>90</sub>	C <sub>100</sub>	Grease lub.	Oil lub.				
110	240	63	57	38	452	563	1 400	1 900			31322JR			
Dimension series to ISO 995 (Refer. 1)	Load center (mm) a	Mounting dimensions (mm)								Constant e	Axial load factors		(Refer. 1) Mass (kg)	
		d <sub>1a</sub> min.	d <sub>1a</sub> max.	D <sub>1a</sub> min.	D <sub>1a</sub> max.	S <sub>1a</sub> min.	S <sub>1a</sub> max.	r <sub>1a</sub> min.	r <sub>1a</sub> max.		Y <sub>1</sub>	Y <sub>0</sub>		
7GB	76.2	128	135	226	205	224	6	21	3	2.5	0.83	0.73	0.40	12.2

## PRODUCT FEATURES

Brand	JTEKT
N° Ean13	3663952411316
Inside diameter	110 mm
Outside diameter	240 mm
Thickness	63 mm
Packaging	1

[contact@123bearing.ie](mailto:contact@123bearing.ie)

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE